

## More personal, More powerful, remarkably thinner and lighter.

- All in one solution, built in 58/80 mm thermal printer and equipped with versatile peripherals for space saving;
- More personal, integrated with versatile peripherals can meet your individual requirements.
- By optical fingerprint scanner which can be safer and reliable to pay.
- Modular design for easy installstion.
- There's so much to say about ZKAIO3000 Series — here are just a few of our favorite things.



## Special Customization Features & Screen

- ZKAIO3000 Series is an intelligent POS System with multiple instrument optional.
- We provide the optional configuration referring to the features of your industry.
- ZKTeco provide the customized POS terminal depending on the screen requirement from clients.



### Optical Fingerprint Scanner

Employee shift is more safety  
Consumers pay is fast and securely





Specifications

Model Name	ZKAIO3000
Fundamental Characteristics	
CPU	Intel Celeron Processor J1900 (Bay-Trail)
Memory	1 x 204 pin DIMM socket up to 8GB DDR3L SDRAM
Storage	HDD(1 x 2.5" SATA drive)
Operating System	Windows Embedded Professional 7
	Windows Embedded Standard 7
	Windows Embedded POSReady 7
	Windows Embedded 8.1 Professional
	Windows Embedded 8.1 Industry
	Windows 10 IoT Enterprise 64 bit
Graphics	Intel Gen 7 Intel Graphics DX 11, OGL3.2
Network	Realtek RTL8111G-CG 10/100/1000
Audio	Realtek ALC662 HD codec

Physical Characteristics

Display	LCD: 15"
	Resolution: 1024 x 768
	Brightness: 250 cd/m² (option:450 cd/m²)
	Touch Screen: 10 points Projective Capacitive
Power Adapter	AC input: 100~240V, 50~60Hz; DC output: 24V / 65W
Physical	LCD Tilting Angle: 15° ~90°
Dimensions	Weight: 9 kg; w/ power adapter, printer (approximate)
	Dimension: 205 (D) x 360 (W) x 426 (H) mm

Work Environment

Operating Temp.	0°~40°C
Storage Temp.	-20°~60°C
Humidity	10% ~ 90%

External I/O Ports

USB Ports	4 x USB 3.0 on the rear and 1x USB 2.0 on the front
Serial Ports	3 x DB-9 (com 1, com 2, and com 3)
	com 1, com 2, and com 3 (RS-232 only) selectable via BIOS seting
	All coms 5V and 12V selectable via jumper seting (default no power)
LAN	1 x RJ-45
PS/2	2 x PS/2 (mouse and keyboard)
Audio	1 x line out, 1 x mic in
VGA	1 x DB-15
Cash Drawer Port	1 x RJ11 output (Printer model only)

Optional

Thermal Printer	Integrated 80/58 mm thermal printer, 200 mm/s auto cutter
MSR	Attached 3 tracks USB type
VFD	Attached 2 x 20 attached VFD
Display	Attached 10.4", XGA 1024 x 768, USB type (Option: 7", 8")
Barcode Scanner	Integrated 1D/2D barcode scanner (alternative of printer)
I-Button	Integrated 1x I button reader

ZKTeco

Focused on Smart Cash Register of Biometrics



ZKAIO3000 Series  
-All In One

Waterproof Biometric Smart POS Terminal

