

iFace880

Multi-Biometric Time Attendance and Access Control Terminal



iFace880 facial multi-biometric time & attendance and access control terminal supports up to 3,000 face templates, 4,000 fingerprint templates and 10,000 cards (optional).

With ZKTeco latest hardware platfrom and algorithm, it offers brand new UI and user-friendly operation interface to provide smooth user experience.

With advanced face algorithm and multi-biometric verification technology, the terminal's security level of verification is significantly enhanced.


Features

- 3,000 face and 4,000 fingerprint templates
- Multi-language
- High verification speed
- Advanced and user-friendly UI
- Optional built-in battery backup, providing approximately 4 hours of continuous operation
- New Framework firmware, easy to extend functions and customize client's requirements
- One face template is registered for one user only
- Able to detect whether the face is an actual face or a photo, enhancing the security level of verification

Specifications

A.3-Inch Touch Screen Face capacity 3,000 (1:N) Fingerprint capacity 4,000 ID Card capacity 10,000 (Optional) Logs capacity 100,000 Communication TCP/IP, USB Host Automatic Status Switch, Self-Service Query, Work Code, SMS, DST, T9 Input, 9 Digit User ID, Scheduled Bell, Photo ID, Wiegand Out, ADMS Optional Functions ID/IC/HID Card, 3G/4G, ADMS, 2000 mAh Backup Battery, External Printer and Bell Power Supply 12V 3A Operating Temperature 0 °C- 45 °C Operating Humidity 20%-80% Dimensions(Length*Width*Thickness) 193.6 × 165 × 111 mm Package Weight(KG) 1.87		
Fingerprint capacity 4,000 ID Card capacity 10,000 (Optional) Logs capacity 100,000 Communication TCP/IP, USB Host Automatic Status Switch, Self-Service Query, Work Code, SMS, DST, T9 Input, 9 Digit User ID, Scheduled Bell, Photo ID, Wiegand Out, ADMS Optional Functions ID/IC/HID Card, 3G/4G, ADMS, 2000 mAh Backup Battery, External Printer and Bell Power Supply 12V 3A Operating Temperature 0 °C- 45 °C Operating Humidity 20%-80% Dimensions(Length*Width*Thickness) 193.6 × 165 × 111 mm	Display	4.3-Inch Touch Screen
ID Card capacity 10,000 (Optional) Logs capacity 100,000 Communication TCP/IP, USB Host Automatic Status Switch, Self-Service Query, Work Code, SMS, DST, T9 Input, 9 Digit User ID, Scheduled Bell, Photo ID, Wiegand Out, ADMS Optional Functions ID/IC/HID Card, 3G/4G, ADMS, 2000 mAh Backup Battery, External Printer and Bell Power Supply 12V 3A Operating Temperature 0 °C- 45 °C Operating Humidity 20%-80% Dimensions(Length*Width*Thickness) 193.6 × 165 × 111 mm	Face capacity	3,000 (1:N)
Logs capacity 100,000 Communication TCP/IP, USB Host Standard Functions Automatic Status Switch, Self-Service Query, Work Code, SMS, DST, T9 Input, 9 Digit User ID, Scheduled Bell, Photo ID, Wiegand Out, ADMS Optional Functions ID/IC/HID Card, 3G/4G, ADMS, 2000 mAh Backup Battery, External Printer and Bell Power Supply 12V 3A Operating Temperature 0 °C- 45 °C Operating Humidity 20%-80% Dimensions(Length*Width*Thickness) 193.6 × 165 × 111 mm	Fingerprint capacity	4,000
Communication TCP/IP, USB Host Automatic Status Switch, Self-Service Query, Work Code, SMS, DST, T9 Input, 9 Digit User ID, Scheduled Bell, Photo ID, Wiegand Out, ADMS Optional Functions ID/IC/HID Card, 3G/4G, ADMS, 2000 mAh Backup Battery, External Printer and Bell Power Supply 12V 3A Operating Temperature 0 °C- 45 °C Operating Humidity 20%-80% Dimensions(Length*Width*Thickness) 193.6 × 165 × 111mm	ID Card capacity	10,000 (Optional)
Automatic Status Switch, Self-Service Query, Work Code, SMS, DST, T9 Input, 9 Digit User ID, Scheduled Bell, Photo ID, Wiegand Out, ADMS Optional Functions ID/IC/HID Card, 3G/4G, ADMS, 2000 mAh Backup Battery, External Printer and Bell Power Supply 12V 3A Operating Temperature 0 °C- 45 °C Operating Humidity 20%-80% Dimensions(Length*Width*Thickness) 193.6 × 165 × 111mm	Logs capacity	100,000
Input, 9 Digit User ID, Scheduled Bell, Photo ID, Wiegand Out, ADMS Optional Functions ID/IC/HID Card, 3G/4G, ADMS, 2000 mAh Backup Battery, External Printer and Bell Power Supply 12V 3A Operating Temperature O°C- 45 °C Operating Humidity 20%-80% Dimensions(Length*Width*Thickness) 193.6 × 165 × 111mm	Communication	TCP/IP, USB Host
Power Supply 12V 3A Operating Temperature 0 °C- 45 °C Operating Humidity 20%-80% Dimensions(Length*Width*Thickness) 193.6 × 165 × 111mm	Standard Functions	
Operating Temperature 0 °C- 45 °C Operating Humidity 20%-80% Dimensions(Length*Width*Thickness) 193.6 × 165 × 111mm	Optional Functions	ID/IC/HID Card, 3G/4G, ADMS, 2000 mAh Backup Battery, External Printer and Bell
Operating Humidity 20%-80% Dimensions(Length*Width*Thickness) 193.6 × 165 × 111mm	Power Supply	12V 3A
Dimensions(Length*Width*Thickness) 193.6 × 165 × 111mm	Operating Temperature	0 °C- 45 °C
	Operating Humidity	20%-80%
Package Weight(KG) 1.87	Dimensions(Length*Width*Thickness)	193.6 × 165 × 111mm
	Package Weight(KG)	1.87

Configuration



What's in the Box

