

ZKBio710P Series

Smart POS Terminal



Features

- All-in-one POS with 15" True-Flat PCAP Touch Screen
- 15" True-Flat PCAP Front Touch Screen with Splash-Proof Protection
- Stylish and Compact Design, Available in Black and Gray & White
- Modular Design Built-in with Fingerprint Module, 2D Barcode Scanning Module and MSR
- Built-in 80mm Thermal Printer
- Hidden Cable Management
- Fanless System with Innovative Heat Pipe Design
- Comprehensive After-Sale Services
- UV Effect Paint Craft

Applications



Retail Outlets



Restaurants



Cafes



Coffee Shops



More

Specifications

Model	ZKBio710P	ZKBio730P	ZKBio750P
Printing method	Intel® Celeron® J1900 @ 1.99GHz Optional: Intel® Celeron® J6412 @ 2.00GHz	Intel® Core® i3-6100U @ 2.40GHz	Intel® Core® i5-6200U @ 2.30GHz
Memory	4GB RAM Standard, DDR3 & DDR4, Up to 8GB 64GB SSD Standard, Up to 512GB Optional: External Memory Slots (M.2 SATA SSD 120GB & HDD 500GB)		
Display	Configuration 1: Main: 15" HD, 1024*768, Capacitive Touch Screen; Second: LED (8C digital tube) Configuration 2: Main: 15" HD, 1024*768, Capacitive Touch Screen; Second: VFD (2*20 lines) Configuration 3: Main: 15" HD, 1024*768, Capacitive Touch Screen; Second: 9.7" LCD HD, 1024*768 Configuration 4: Main: 15" HD, 1024*768, Capacitive Touch Screen; Second: 15" LCD HD, 1024*768		
Material	Aluminum alloys, ABS		
Colour	Black and Gray, White (Optional)		
Operating System	Support Windows 7, 8, 10, 11		
Dimension	346*190*402mm		
Packing Dimension	405*300*450mm		
Net Weight	Configuration 1&2: 5.9Kg Configuration 3: 6.8Kg Configuration 4: 8.2Kg		
Gross Weight	Configuration 1&2: 7.5Kg Configuration 3: 8.4Kg Configuration 4: 9.8Kg		
Interface (s)	1* USB 3.0 5* USB 2.0 1* RJ45 LAN port 1* COM port 1* VGA port 1* Audio jack 1* MIC IN 1* Power port	4* USB 3.0 2* USB 2.0 2* COM port 1* VGA port 1* HDMI port 1* RJ45 LAN port 1* Audio jack 1* MIC IN 1* Power port	4* USB 3.0 2* USB 2.0 2* COM port 1* VGA port 1* HDMI port 1* RJ45 LAN port 1* Audio jack 1* MIC IN 1* Power port
Power Supply	DC12V/5A		
WiFi	Single-band 2.4GHz (Optional) Dual-band 2.4GHz/5GHz (Optional)		
Bluetooth	Not Support		
Printer	Built-in 80mm thermal printer Built-in 58mm thermal printer (Optional)		
Peripherals (Optional)	Built-in fingerprint module Built-in 2D barcode scanning module Built-in MSR reader Built-in RFID reader		
Operating Temperature	0°C ~ 40°C at 20% ~ 80% Humidity		
Storage Temperature	-15°C ~ 60°C at 20% ~ 80% Humidity		
Certification (s)	ISO9001, CE, FCC, RoHS		

