

BLADE6040

Screener Assist X-ray Baggage Inspection Systems



BLADE6040 is a X-ray baggage inspection which has a tunnel size of 610 mm by 420 mm and can provide the effective inspection of mail, hand-held baggage, luggage and other items. It allows identification of weapons, liquids, explosives, drugs, knives, fire guns, bombs, toxic substances, flammable substances, ammunition, and dangerous objects, which are safety hazard by identification of substances with effective atomic number.

High image quality in combination with automatic identification of suspicious objects allows the operator to quickly and effectively evaluate any luggage content.

Features

- Real-time Detection to Aid Operators in Identifying Suspicious
- High Performance Typical Penetration up to 40 mm of Steel
- Startup with Fingerprint
- Four Layers of Lead Curtain
- Equipped with Input & Output Rollers
- Adjustable Conveyor Speed
- Real Time Remote Monitoring System
- Luggage Image and Walk Through Metal Detector Status Display on the Same Screen
- Threat Image Projection (TIP)

Options

- Gray Painting
- Passenger-package linkage

Specifications (GGL Exclusive Feature)

Technical Characteristics:

Tunnel Dimensions(W*H): 610mm*420 mm

G Conveyor Speed: 0.20 m/sec ~ 0.40m/sec

Load on Conveyer:

Max 200 kg (Evenly Distributed)

Space Defintion:

HorizontalΦ1.0mm VerticalΦ1.0mm

- **G** Steel Penetration: 40mm
- **ு** Wire Resolution: 38AWG

Dual-energy detector: Yes

Number of Colors in X-ray Image: 3

Dimensions(L*W*H):

1987.5*1023.9*1317mm

Package Dimensions(L*W*H):

2600mm*1250mm*1600mm

Package Weight: 750kg

Film Safety: ASA/ISO1600 standard of film safety

Radiation Leak Dosage: 0.1µ Gy/h (5cm from the

surface)

Operating Environment:

Operating Temperature: -10°C to +45°C Storage Temperature: -20°C to +60°C

Humidity: 5-95%, non condensing

Power Supply:230 VAC +/- 10% / 60/50 Hz (EU) 110 VAC +/- 10% / 60/50 Hz (US)

Power Consumption: 700W Sound Pressure: <51.8dB (A)

X-ray Generator:

- G Tube Current: 0.5-1.0 mA(adjustable)
- ♠ Anode Voltage: 150-170 kV(adjustable) Generator Cool: Seal oil cooling / 100%

Computer Specification:

Monitor: 21.5" LED color Processor: i3-3220 RAM: 4 GB DDR3

Hard Drive: 120GB SSD+1TB HDD

Graphic Card: GT730-2G

Software features:

Perfect View (PV)

Black / White (B/W)

Pseudo Colors (PS)

Inverse View (IN)

High Penetration (HP)

Real Time Image Processing

Image Zoom(128x)

Image of Previous Baggage

Programmable Function Keys

Baggage Counter

Date / Time Indicator


Threat Image Projection (TIP)

▶ Intelligent Analysis Function

Platform software: ZKBio SIS

metal detector

Dimensions (mm)





ZKTECO CO.,LTD. www.zkteco.com E-mail: sales@zkteco.com





Copyright © 2024 ZKTECO CO., LTD. All rights reserved V2.4 2024.12.02