

# Z8632NFR-S | ZKBio Sense Series

## H.265+ 32 Channels ZKBio Sense Smart Network Video Recorder



- Supports H.265+, H.265, and H.264 video formats with enhanced decoding performance
- Compatible with up to 12MP IP cameras inputs
- Supports 16-channels realtime playback synchronously
- 2 SATA Port, up to 16 TB storage capacity
- HDMI (4K) and VGA (1080p) outputs with independent simultaneous display capability
- Embedded intelligent classification algorithm based on computer vision technology for human/ vehicle classification
- Multiple intelligent video analytics functions (NVR local intelligence)
- Supports multiple web browsers login
- P2P cloud service supported
- Compatible with ONVIF Profile S/T/G



Target Counting



Line Crossing



Intrusion Detection



Motion Detection



Object Left / Remove

### Product Overview

ZKBio Sense smart network video recorder (NVR) enhances the efficiency and safety of video surveillance system. ZKBio Sense smart NVR features a powerful CPU hardware and ZKTeco's intuitive graphical operating system, these recorders provide 24/7 continuous recording of all video channels and intelligent alarm events. The system automatically classifies and stores footage by human and vehicle detection on the hard drive. Moreover, an advanced retrieval functions enable rapid playback of specific targets (human/ vehicle), allowing users to quickly locate critical footage and alarm events.

ZKBio Sense smart NVR enhances surveillance system efficiency and safety across diverse applications including educational facilities, corporate offices, industrial parks, residential communities, and public security operations.

### Core Features

#### H.265+

H.265+ is an optimization of the H.265 algorithm. Through technologies such as dynamic bitrate control and scene-adaptive encoding, it reduces the required bitrate by 20% - 40% compared with H.265 while maintaining the same video quality.

#### Intelligent Video Analytics (IVA)

ZKBio Sense Network Video Recorders support multiple intelligent video analytic functions, such as: Line Crossing, Area Detection, Target Counting, Counting Statistics, Object Lost/Left, Smart Motion Detection base on human and vehicle targets classification.

#### Smart Retrieval

ZKBio Sense Network Video Recorders support smart retrieval for video and alarm events by human & vehicle classification, enabling users to efficiently search and locate the targeted video clips and alarm events.

#### ANR (Only for SD card IPC models)

When the connection between IPC and NVR is lost, the video is saved in the SD card. The saved video is automatically transferred to the NVR when network connection is restored, preventing any video loss.

#### Alarm Push Notification

When the NVR receives alarm events, it can trigger actions including email, alarm alerts and buzzer activation. Also, the alarm messages are pushed to mobile app and management platform software in real-time.

## Technical Parameters


Model	Z8632NFR-S
System	
Main Processor	Multi-core embedded processor
Operating System	Embedded LINUX
Video and Audio	
Max. IPC Video Input	32CH
Two-way Talk	Support
Audio Compression	G.711u
Max. Audio Input	32CH by IPC
Third Party Camera Access	ONVIF & RTSP
Live View	
Display Split	1/4/6/8/9/16/32CH
Resolution	12MP(4000*3000)/8MP(3840*2160)/6MP(3288*1850)/5MP(2592*1944)/4MP((2560*1440)/3MP(2304*1296)/2MP(1920*1080)/1.3MP(1280*1024)/ 1MP(1280*720)/D1(1024*768)
Max. Live View Capability	Local AI OFF:2CH@12MP, 4CH@6MP/5MP,6CH@4MP,8CH@2MP,9CH@2MP,16CH@720P,32CH@D1 Local AI ON:2CH@12MP, 4CH@6MP/5MP,6CH@4MP,8CH@2MP,9CH@2MP,16CH@720P,32CH@D1
Recording	
Video Compression	H.265+ / H.265 / H.264
Recording Resolution	12MP/8MP/6MP/5MP/4MP/1080P/960P/720P/D1/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Max. Decoding Capability	Local AI OFF:2CH@12MP, 4CH@6MP/5MP,6CH@4MP,8CH@2MP,9CH@2MP,16CH@720P,32CH@D1 Local AI ON:2CH@12MP, 4CH@6MP/5MP,6CH@4MP,8CH@2MP,9CH@2MP,16CH@720P,32CH@D1
Incoming Bandwidth	Local AI OFF:256Mbps Local AI ON:250Mbps
Outgoing Bandwidth	Local AI OFF:128Mbps Local AI ON:128Mbps
Stream Type	Video, Video & Audio
Bit Rate	Main Stream: 16Kbps ~ 12288Kbps Sub Stream: 16Kbps ~ 4096Kbps
Storage Method	Local hard drive and network
Record Mode	Schedule, Manual, Motion Detection, IVA Events Alarm
Record Interval	1 ~ 120 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 1~ 10 min
Playback and Backup	
Playback Channel	16CH synchronously playback
Search Mode	Time / Date, Alarm Types, IVA Search
Playback Function	Play, Stop, Play Forward, Play Backward, 30 Seconds Forward, 30 Seconds Backward, Fast Play, Slow Play, Single Frame Play, Hide/Show Time Bar, Backup, Snapshot, Full Screen
Backup Mode	USB Device / Network Remote
Intelligent Video Analytics	
IVA by Camera	Line Crossing, Area Detection, Smart Motion Detection (base on human and vehicle classification), Target Counting, Object Lost/Left, Fire Detection, Temperature Measurement, Heat Point Detection, Smoking Detection
Local IVA Functions	Line Crossing, Area Detection, Smart Motion Detection (base on human and vehicle classification), Target Counting, Counting Statistics, Object Lost/Left
IVA by Device (Number of Channels)	2
IVA by Camera (Number of Channels)	32
IVA Alarm	
Smart IVA Alarm	Line Crossing, Area Detection, Smart Motion Detection, Target Counting, Object Lost/Left, Fire Detection, Temperature Measurement, Heat Point Detection, Smoking Detection

<b>Regular Detection</b>	Motion Detection / Video Shelter / Video Loss / Privacy Mask
<b>Anomaly Alarm</b>	HDD Full, No HDD, S.M.A.R.T error, Network disconnected, IP conflict
<b>Alarm Linkage</b>	Preview, Recording, Snapshot,Buzzer, Preset, Email, Tour, Upload center
<b>Smart Search</b>	Support smart search out target video by human and vehicle classification filtering
<b>Network</b>	
<b>Network Protocol</b>	TCP/IP, HTTP,HTTPS, ONVIF, DHCP, DNS, DDNS, RTSP, NTP, UPnP, SMTP, IPv4, IPV6,UDP, SSL/TLS, PPPoE, WebSocket, ICMP, IGMP, RTMP, RTP, RTCP, ARP
<b>Max. Online User</b>	30
<b>Web Browser</b>	Google Chrome/Microsoft Edge/Firefox/Safari
<b>Operation System</b>	Windows
<b>Management Platform</b>	ZKBio CVSecurity / CVAccess / AntarVis 2.0
<b>Mobile Application</b>	AntarView Plus (iOS & Android)
<b>P2P Cloud Service</b>	Support OTA updates via the AntarView Plus
<b>Interoperability</b>	ONVIF Profile S/T/G, SDK, CGI, API
<b>Storage &amp; Auxiliary Interface</b>	
<b>SATA Ports</b>	2 SATA Port, up to 16 TB storage capacity
<b>eSATA</b>	N/A
<b>Raid 0/1/5/6/10</b>	N/A
<b>HDMI</b>	1*HDMI (4K)
<b>VGA</b>	1*VGA(1920*1080/60Hz, 1280*1024/60Hz)(support independent output)
<b>Network Interface</b>	1 RJ-45 Port (10/100/1000 Mbps self adaptive )
<b>PoE Ports</b>	N/A
<b>Standard</b>	N/A
<b>USB</b>	2*USB 2.0,1*USB 3.0
<b>Audio Input/Output</b>	1 In / 1 Out
<b>Alarm Input/Output</b>	4 In / 2 Out
<b>RS-485</b>	Support
<b>RS-232</b>	N/A
<b>Power</b>	
<b>Power Supply</b>	DC 12V/5A
<b>Power Consumption</b>	≤24W (withoutHDD)
<b>General</b>	
<b>Casing</b>	1.5U
<b>Working Temperature</b>	-10°C ~ 55°C / 14°F ~ 131°F
<b>Working Humidity</b>	10% ~ 90%
<b>Storage Humidity</b>	10% ~ 90%
<b>Operating Altitude</b>	3,000 m (9,842.52 ft)
<b>Installation</b>	Desktop / Cabinet mount
<b>Dimensions(L*W*H)</b>	325*307*52(mm)
<b>Net Weight</b>	3KG(without HDD)
<b>Gross Weight</b>	3.5KG(without HDD)
<b>Certifications</b>	CE-LVD; CE-EMC; FCC certification
<b>Environment</b>	CE-RoHS, WEEE, Reach self-declaration

## Ordering Information

Name	Model	Description
ZKBio Sense Smart NVR	Z8632NFR-S	32CH H.265+ 4K NVR, 2 SATA

## Dimension (mm)



## Rear Panel

